

Data Sheets



SPECIALTY PANELS

FurniLite™ (superlight blockboard)

Sizes FurniLite™ Fromager: 1860 x 3640 mm , 1220 x 2520 mm
FurniLite™ Okoume: 3100 x 1530 mm, 2500x 1220 mm
FurniLite™ Paper: 1860 x 3640 mm, 1220 x 2520 mm

Weight 300 kg/m³ (FurniLite™ Fromager)
350 kg/m³ (FurniLite™ Okoume)

Gluing Class 3 - E1
Melamine adhesive
Components Gluing E0



TECHNICAL SPECIFICATIONS OF FURNILITE™ FROMAGER

Thickness	Weight	Bending Strength		Screw Withdrawal Strength
mm	kg/m ²	N/mm ²		daN
		Long Grain	Cross Grain	
14	4,2			
16	4,8	29,5	4860	93
19	5,7	34,0	6670	108
25	7,5			
30	9,0			

TECHNICAL SPECIFICATIONS OF FURNILITE™ OKOUME

Thickness	Weight
mm	kg/m ²
16	5,6
19	6,7

TECHNICAL SPECIFICATIONS OF FURNILITE™ PAPER

Thickness	Weight
mm	kg/m ²
14	4,2
16	4,8
19	5,7
25	7,5
30	9,0

Dimensional tolerances comply with the requirements of standard EN 315. Customized thicknesses and configurations upon request.

NOTES

Dotted lines for writing notes.